



AP24455K LED Panel High

Break through LED light replacing 128 watts fluorescent T8. Ultra low profile less than 3 inches high. No glare and very low temperature operation allows direct wall or suspended mount. Instant on or dimming operation available. Save 50% energy over T8.



AP24455K		
	100V - 240V	
	45 WATTS	
	4,000 LM 93 L/W	IP65
	5,000 - 5,500K CCT	83+ CRI
	2' x 2' x 2.5"	
	80,000 HOURS	
	White	
	4 Lbs 1.8 KG	
	Five Year Warranty	



Small footprint makes fixture easy to handle and can be mounted by conduit or by hook.



83+ CRI TrueColor Technology



Amerlight's LED Brightest in the Industry



Wireless Controls Available

Designed and Assembled in the USA



AMERLIGHT
Advanced LED Technology

amerlight.com
9200 Petersburg Road
Evansville, IN 47725

MORE LIGHT

LESS ENERGY

LOWER COST



Five Year Warranty



LED to Metal Halide,
5 to 1 Ratio in Watt
to Watt Savings



Installation

1. Use a qualified electrical contractor and follow all applicable electrical codes.
2. Attach aircraft hanger wire to the joist or other secure mounting location.
3. Adjust length of wire to achieve the required height and angle from the floor.
4. Properly secure the wire.
5. Please insure that hanger wire meets all local seismic applicable codes.



AMERLIGHT
Advanced LED Technology

amerlight.com
9200 Petersburg Road
Evansville, IN 47725