



AP24755K LED Panel High

Break through LED light replacing 128 watts fluorescent T8. Ultra low profile panel is less than half inch high. No glare and very low temperature operation allows direct wall or suspended mount. Instant on or dimming operation available. Save 50% energy over T8.



AP24755K	
	100V - 277V
	75 WATTS
	7,500 LM 100 L/W IP20
	5,000 - 5,500K CCT 83+ CRI
	2' x 4' x 2.5"
	80,000 HOURS
	White
	4 Lbs 1.8 KG
	Five Year Warranty



Small footprint makes fixture easy to handle and can be mounted by conduit or by hook.



83+ CRI
TrueColor
Technology



Amerlight's
LED Brightest
in the Industry



Wireless
Controls
Available

Designed and Assembled in the USA



AMERLIGHT

Advanced LED Technology

amerlight.com

MORE LIGHT

LESS ENERGY

LOWER COST



Five Year Warranty



LED to Metal Halide,
5 to 1 Ratio in Watt
to Watt Savings



Installation

1. Use a qualified electrical contractor and follow all applicable electrical codes.
2. Attach aircraft hanger wire to the joist or other secure mounting location.
3. Adjust length of wire to achieve the required height and angle from the floor.
4. Properly secure the wire.
5. Please insure that hanger wire meets all local seismic applicable codes.



AMERLIGHT
Advanced LED Technology

amerlight.com